## **TOSHIBA**

## E-STUDIO2822AF

# Size Does Not Matter. Small but Reliable.













COPY SPEED



#### A3 With A Small Footprint







A compact machine which supports up to A3 size paper, all packed in a small A4 sized footprint.

#### Low Total Cost of Ownership (TCO)

Due to its size and functionality, this series offers a low total cost of ownership (TCO) as when compared with similar footprint products!



#### Reliable and Durable

No matter the environment, this series continually performs at its best so that productivity will never be compromised.



#### Special Media Print

Forms and labels can be printed for shipments, as well as waterproof paper printing capabilities to help in and around the workplace!



SPECIFICATION for		e-STUDIO2822AF
GENERAL ———		
Copying/Printing Process		Indirect electrostatic photographic method
Print & Copy Speed		28ppm (A4 size), 14ppm (A3 size via Bypass)/28cpm (A4 size)
Warm-up Time		Approx.18 seconds
Paper Size & Weight		Drawer: A4 (64 - 80gsm)
		Stack Feed Bypass: A3/A5-R (52 - 216gsm)
Paper Capacity		Drawer: 250 sheets
		Stack Feed Bypass: 50 sheets
Max. Paper Capacity		300 sheets
Paper Exit		Face down/Inner exit (100 sheets)
Processor Memory		Cortex A8 500MHz 512MB
Dimensions		512/m W390 x D540 x H505 (mm)
Control Panel		w 390 x D340 x T300 (limit) LCD - W45 x H27 (mm) with Back light and Key top
Weight (Approx.)		28.5kg
Power Consumption		1.5kW (220-240V)
Operation Noise		64.75dB[A]
Special Features		Auto Power Save, Auto Sleep Mode, Energy Saver
oposiai i oasai so		
COPY —		
Max. Original Size		A3 (A4 on platen glass)
Resolution		2400dpi x800dpi (with smoothing)
Multiple Copy Qty		2-roopy a coopy with since may
First Copy		Less than 6.4 seconds (A4 size from 1st drawer, 100%)
Zoom		25% to 400% (1% Increment)
Copy Mode		Text, Text/Photo (Default), Photo, Background Erase
Image Density Control		Automatic/Manual (9 Steps)
PRINT -		
Resolution		2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit)
Page Description Language		PCL6 (PCL XL), PCL5e, PCL5c
Operating Systems		Windows 7 SP1 (32/64 bit)(Recommended)
1 3 7		Windows 8.1 (32/64 bit)
		Windows 10
		Redstone 5
		Windows Server 2008 SP2 (32/64 bit)/R2 SP1 (64 bit)
		Windows Server 2012/R2 (64 bit)
		Windows Server 2016
		Mac OS 10.11, 10.12, 10.13, 10.14
		Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Version 42.3, Bharat Operating System 6.x
Interface		RJ45/USB 2.0
Network Protocol		TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP
Print Protocol		LPR/LPD, Port 9100 (bi-directional), IPP ver1.1
Print Function		Toner Save Mode, Watermark, Multiple Pages Per Sheet, USB Direct Printing
Mobile Print		App (eBPC Entry), USB Connection
2044		
SCAN —		
Resolution		600 x 600dpi
Scan Speed		Up to 25spm (with RADF)
Scan Modes		B&W, Greyscale, Colour
File Formats		B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page
		Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
Coon Amount		Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page
Scan Agent		Scan to USB/Mobile, Scan to File (SMB/FTP), Scan to Email
Mobile Scan		App (eBPC Entry), USB Connection
FAX —		
Compatibility		ECM, Super G3, G3
Data Compression Method		E.U., Super G.S., G.S. JBIG, MMR, MR, MH
Modem Speed		JOICE, MINITE, MIN, MIN. 33.6Kbps – Z.4Kbps (Auto Fallback)
Transmission Speed		333xxyp = 2-recup (recut i alineatic) Approx. 3 sec.
Broadcast Transmission		Max. 256 jobs, 220 destinations/job, Max. 384 pages/file
		, and the second
OPTIONS —	1	
Wireless LAN Module	GN-1160/C	<b>√</b>
Harness Kit for	GQ-1131	V
Coin Controller		
Front Cover	KK-2505	V
Customisation Vit	1	

MH-2505

Customisation Kit

### TOSHIBA

Toshiba Tec Malaysia Sdn. Bhd. Registration No.: 198101000677 (66785-D)

No. 5, Jalan Jurubina U1/18, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel: +603-5568 7788 Service: +603-5568 7699

Website: www.toshibatec.com.my

Fax: +603-5568 7700