

TOSHIBA

e-STUDIO2329A/2829A

Compact. Efficient. Functional.



COPY



PRINT



A3



DUPLEX



COLOUR
SCAN



COPY
SPEED



TOGETHER
INFORMATION


Enhanced without compromise

Offers enhancements on operability, usability and environmental regulations without the compromise of size and speed.




ID Card Copying

Conveniently copy both sides of an ID card-sized document for improved productivity!



Email Notifications

Notifications via email will be directly sent to an indicated address when a change of toner cartridge is needed!



Mobile Scan/Print

Printing is even more hassle-free now! Simply connect and print or scan directly from your mobile phone!

*Available on Android OS only



SPECIFICATION for		e-STUDIO2329A/2829A
GENERAL		
Copying/Printing Process	Indirect electrostatic photographic method	
Print & Copy Speed	23/28cpm (A4)/14cpm (A3)	
Warm-up Time	Approx.15 seconds	
Paper Size & Weight	Drawer: A3/A5-R (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)	
Paper Capacity	Drawer: 250 sheets Stack Feed Bypass: 100 sheets	
Max. Paper Capacity	1700 sheets	
Paper Exit	Face down/Inner exit (100 sheets)	
Processor	Cortex A8 500MHz	
Memory	512MB / 1GB (Opt. PS option)	
Dimensions	W575 x D540 x H402 (mm)	
Control Panel	LCD - W66 x H35 (mm) with Back light and Key top	
Weight (Approx.)	27kg	
Power Consumption	Max. 1.5kW (220 - 240V)	
Operation Noise	64.75dB[A]	
Special Features	Auto Power Save, Auto Sleep Mode, Energy Saver	
COPY		
Max. Original Size	A3	
Resolution	2400dpi x 600dpi (with smoothing)	
Multiple Copy Qty	1-999/Ten key input	
First Copy	Less than 6.4 seconds (A4 size from 1st drawer, 100%)	
Zoom	25% to 400% (1% Increment)	
Copy Mode	Text, Text/Photo(Default), Photo, Background Erase	
Image Density Control	Automatic / Manual (9 Steps)	
PRINT		
Resolution	2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit)	
Page Description Language	PCL5e/ PCL5c/ PCL6 (PCL XL)/ PS3 Emulation (Opt.)	
Operating Systems	Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8.1 (32/64 bit) Windows 10 Redstone 5 Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Windows Server 2016 Mac OS 10.11, 10.12, 10.13, 10.14 Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Leap 42.3 / Bharat Operating System 6.x	
Interface	RJ45/USB 2.0	
Network Protocol	TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP	
Print Protocol	LPR/LPD, Port 9100 (bi-directional), IPP ver1.1	
Print Function	Toner Save Mode, Watermark, Multiple Pages Per Sheet	
Mobile Print	App (eBPC Entry), USB Connection	
SCAN		
Resolution	Up to 600 x 600dpi	
Scan Speed	Up to 25spm	
Scan Modes	B&W, Greyscale, Colour	
File Formats	B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page	
Destination Support	File Server, SMB, FTP, Scan to File, Scan to Email Scan to USB/TWAIN	
FAX		
Compatibility	Super G3, G3	
Data Compression Method	JBIG, MMR, MR, MH	
Modem Speed	33.6kbps -- 2.4Kbps (Auto fallback)	
Transmission Speed	Approx. 3 sec.	
Broadcast Transmission	Max. 256 jobs, 220 destinations/job, Max. 384 pages/file	
OPTIONS		
Document Feeder (RADF)	MR-3032	✓
Platen Cover	KA-2507PC	✓
Paper Feed Unit	MY-1043-B	✓
Desk	MH-2506	✓
Harness Kit for Coin Controller	GQ-1131	✓
Auto Duplex Unit	MD-0107	N.A (Standard)
Paper Feed Pedestal	KD-1039-B	✓
Drawer Module	MY-1044-B	✓
FAX Kit	GD-1380	✓
Wireless LAN Module	GN-1160	✓
PS module + 1GB memory (es2329A)	GA-1350L	✓
PS module + 1GB memory (es2829A)	GA-1350H	✓

Distributed by

TOSHIBA

Toshiba Tec Malaysia Sdn. Bhd.

Registration No.: 198101000677 (66785-D)

No. 5, Jalan Jurubina U1/18, Seksyen U1,
Hicom Glenmarie Industrial Park,
40150 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel : +603-5568 7788 Service : +603-5568 7699 Fax : +603-5568 7700
Website : www.toshibatec.com.my

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved.