

TOSHIBA

e-STUDIO2329A/2829A

Compact. Efficient. Functional.



COPY



PRINT



A3



DUPLEX



COLOUR
SCAN



23/28
BW CPM
COPY
SPEED



TOGETHER
INFORMATION

Enhanced without compromise

Offers enhancements on operability, usability and environmental regulations without the compromise of size and speed.




ID Card Copying

Conveniently copy both sides of an ID card-sized document for improved productivity!



Email Notifications


Notifications via email will be directly sent to an indicated address when a change of toner cartridge is needed!



Mobile Scan/Print

Printing is even more hassle-free now! Simply connect and print or scan directly from your mobile phone!

*Available on Android OS only



| SPECIFICATION for | | e-STUDIO2329A/2829A |
|----------------------------------|--|---------------------|
| GENERAL | | |
| Copying/Printing Process | Indirect electrostatic photographic method | |
| Print & Copy Speed | 23/28cpm (A4)/14cpm (A3) | |
| Warm-up Time | Approx.15 seconds | |
| Paper Size & Weight | Drawer: A3/A5-R (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm) | |
| Paper Capacity | Drawer: 250 sheets Stack Feed Bypass: 100 sheets | |
| Max. Paper Capacity | 1700 sheets | |
| Paper Exit | Face down/Inner exit (100 sheets) | |
| Processor | Cortex A8 500MHz | |
| Memory | 512MB / 1GB (Opt. PS option) | |
| Dimensions | W575 x D540 x H402 (mm) | |
| Control Panel | LCD - W66 x H35 (mm) with Back light and Key top | |
| Weight (Approx.) | 27kg | |
| Power Consumption | Max. 1.5kW (220 - 240V) | |
| Operation Noise | 64.75dB(A) | |
| Special Features | Auto Power Save, Auto Sleep Mode, Energy Saver | |
| COPY | | |
| Max. Original Size | A3 | |
| Resolution | 2400dpi x 600dpi (with smoothing) | |
| Multiple Copy Qty | 1-999/Ten key input | |
| First Copy | Less than 6.4 seconds (A4 size from 1st drawer, 100%) | |
| Zoom | 25% to 400% (1% Increment) | |
| Copy Mode | Text, Text/Photo(Default), Photo, Background Erase | |
| Image Density Control | Automatic / Manual (9 Steps) | |
| PRINT | | |
| Resolution | 2400dpi x 600dpi (with smoothing), 600dpi x 600dpi (1 bit) | |
| Page Description Language | PCL5e/ PCL5c/ PCL6 (PCL XL)/ PS3 Emulation (Opt.) | |
| Operating Systems | Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8.1 (32/64 bit) Windows 10 Redstone 5 Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Windows Server 2016 Mac OS 10.11, 10.12, 10.13, 10.14 Linux / Redhat Enterprise 5.10.x, 6.5.x, 7.4X / Fedora Version 27 / Open SuSE Leap 42.3 / Bharat Operating System 6.x | |
| Interface | RJ45/USB 2.0 | |
| Network Protocol | TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP | |
| Print Protocol | LPR/LPD, Port 9100 (bi-directional), IPP ver1.1 | |
| Print Function | Toner Save Mode, Watermark, Multiple Pages Per Sheet | |
| Mobile Print | App (eBPC Entry), USB Connection | |
| SCAN | | |
| Resolution | Up to 600 x 600dpi | |
| Scan Speed | Up to 25spm | |
| Scan Modes | B&W, Greyscale, Colour | |
| File Formats | B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale : JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page | |
| Destination Support | File Server, SMB, FTP, Scan to File, Scan to Email Scan to USB/TWAIN | |
| FAX | | |
| Compatibility | Super G3, G3 | |
| Data Compression Method | JBIG, MMR, MR, MH | |
| Modem Speed | 33.6kbps -- 2.4Kbps (Auto fallback) | |
| Transmission Speed | Approx. 3 sec. | |
| Broadcast Transmission | Max. 256 jobs, 220 destinations/job, Max. 384 pages/file | |
| OPTIONS | | |
| Document Feeder (RADF) | MR-3032 | ✓ |
| Platen Cover | KA-2507PC | ✓ |
| Paper Feed Unit | MY-1043-B | ✓ |
| Desk | MH-2506 | ✓ |
| Harness Kit for Coin Controller | GG-1131 | ✓ |
| Auto Duplex Unit | MD-0107 | N.A (Standard) |
| Paper Feed Pedestal | KD-1039-B | ✓ |
| Drawer Module | MY-1044-B | ✓ |
| FAX Kit | GD-1380 | ✓ |
| Wireless LAN Module | GN-1160 | ✓ |
| PS module + 1GB memory (es2329A) | GA-1350L | ✓ |
| PS module + 1GB memory (es2829A) | GA-1350H | ✓ |

Distributed by

TOSHIBA

Toshiba Tec Malaysia Sdn. Bhd.

Registration No.: 198101000677 (66785-D)

4, Jalan Saudagar U1/16, Seksyen U1, Hicom Glenmarie Industrial Park, 40150, Shah Alam, Selangor Darul Ehsan, Malaysia.

(P.O. Box 7722, Pejabat Pos Besar, 40724 Shah Alam, Selangor Darul Ehsan, Malaysia.)

Tel : +603-5568 7788 Service : +603-5568 7699 Fax : +603-5568 7700

Website : www.toshibatec.com.my

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved.